

SAFETY DATA SHEET

Staycell ONE STEP® 502 A-Isocyanate

Prepared in accordance with the United States Hazard Communication Standard: 29 CFR 1910.1200

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product Name: Staycell ONE STEP® 502 A-Isocyanate

Chemical Name: Polymeric Methylene Diphenyl Diisocyanate (pMDI)

Recommended Use: Component of a Spray-Applied Polyurethane Foam Insulation System

Manufactured By: Preferred Solutions, Inc.
5000 Rockside Road, Suite 230
Independence, OH 44131
Tel: 800-522-4522
Fax: 216-642-1166

Emergency Contact: PERS (US): 24 hours/7 days
800-633-8253 Domestic
801-629-0667 International

2. HAZARDS IDENTIFICATION

GHS-US classification:

Specific Target Organ Toxicity - Single Exposure (Respiratory System) - Category 3
Specific Target Organ Toxicity - Repeated Exposure (Respiratory Tract) - Category 1
Skin Irritation - Category 2
Eye Irritation - Category 2B
Respiratory Sensitization - Category 1
Skin Sensitization - Category 1
Carcinogenicity - Category 2
Acute Toxicity (Inhalation) - Category 4

Pictograms:



GHS08



GHS07

Signal Word

Danger

SAFETY DATA SHEET

Staycell ONE STEP® 502 A-Isocyanate

Hazard Statements - Health:

- H315 - Causes skin irritation.
- H317 - May cause an allergic skin reaction.
- H319 - Causes serious eye irritation.
- H332 - Harmful if inhaled.
- H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 - May cause respiratory irritation.
- H351 - Suspected of causing cancer.
- H373 - May cause damage to organs through prolonged or repeated exposure.

Precautionary Statements - General:

- P101 - If medical advice is needed, have product container or label at hand.
- P102 - Keep out of reach of children.
- P103 - Read label before use.

Precautionary Statements - Prevention:

- P202 - Do not handle until all safety precautions have been read and understood.
- P233 - Keep container tightly closed.
- P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.
- P264 - Wash thoroughly after handling.
- P271 - Use only outdoors or in a well-ventilated area.
- P272 - Contaminated work clothing must not be allowed out of the workplace.
- P280 - Wear protective gloves/protective clothing/eye protection/face protection.
- P284 - In case of inadequate ventilation wear respiratory protection.

Precautionary Statements - Response:

- P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P342 + P311 - IF EXPERIENCING RESPIRATORY SYMPTOMS: Call a POISON CENTER/doctor.
- P304 + P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P302 + P352 - IF ON SKIN: Wash with plenty of water.
- P312 - Call a POISON CENTER/doctor if you feel unwell.
- P362 + P364 - Take off contaminated clothing. Wash contaminated clothing before reuse.
- P308 + P313 - If exposed or concerned: Get medical attention/advice.
- P332 + P313 - If skin irritation occurs: Get medical attention/advice.
- P333 + P313 - If skin irritation or rash occurs: Get medical attention/advice.
- P337 + P313 - If eye irritation persists: Get medical attention/advice.
- P321 - Specific treatment (see Section 4 of this SDS).
- P314 - Get medical attention/advice if you feel unwell.

Precautionary Statements - Storage:

- P405 - Store locked up.
- P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.

Precautionary Statements - Disposal:

- P501 - Dispose of contents/container to an approved waste disposal plant.

SAFETY DATA SHEET

Staycell ONE STEP® 502 A-Isocyanate

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance/Mixture: Mixture

Hazardous Components

Chemical Name	CAS Number	% Content
Polymeric Diphenylmethane Diisocyanate (pMDI)	9016-87-9	<55%
Diphenylmethane-4,4'-diisocyanate (MDI)	101-68-8	38%
MDI Mixed Isomers	26447-40-5	<10%

4. FIRST AID MEASURES

General Information:

Symptoms of exposure may occur after several hours; therefore medical observation for at least 48 hours after exposure. First Aid responders should pay attention to self-protection and use the recommended protective clothing. If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Eyes:

In case of contact, hold eyelids apart and immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.

Skin:

Remove contaminated clothing and shoes. Wash clothing before reuse. Wash affected areas with soap and water. Get medical attention immediately if irritation (redness, rash, blistering) develops and persists.

Ingestion:

DO NOT INDUCE VOMITING UNLESS DIRECTED TO DO SO BY MEDICAL PERSONNEL. Never give anything by mouth to an unconscious victim. Get medical attention immediately.

Inhalation:

Remove the person from the contaminated area to fresh air. If breathing is difficult, give oxygen. Do not allow victim to move about unnecessarily. Symptoms of pulmonary edema or asthmatic symptoms may develop and may be immediate or delayed up to several hours. Get medical attention immediately.

Information for Doctor:

Symptomatic treatment and supportive therapy as indicated. Following severe exposure the patient should be kept under medical review for at least 48 hours.

Most important symptoms and effects, both acute and delayed:

Eye Contact: Adverse symptoms may include the following: pain or irritation, watering, redness

Inhalation: Adverse symptoms may include: Respiratory tract irritation, coughing, wheezing and breathing difficulties, asthma.

Skin Contact: Adverse symptoms may include the following: irritation, redness.

Ingestion: No specific data

Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media:

Dry chemical powder, Carbon dioxide (CO₂), foam, water fog or fine spray. Alcohol resistant foams are preferred for large fires. Use water spray to cool fire exposed containers.

SAFETY DATA SHEET

Staycell ONE STEP® 502 A-Isocyanate

Unsuitable extinguishing agents:

Water may be used if no other media is available and then in copious quantities. Reaction between water and hot isocyanate may be vigorous. Prevent washings from entering water courses.

Special hazards arising from the substance or mixture:

In a fire or if heated, a pressure increase will occur and the container may burst. Combustion products may include carbon monoxide, carbon dioxide, nitrogen oxides, isocyanates and isocyanic acids.

Advice for firefighters:

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk without suitable training. Stay up-wind and keep out of low areas where gases (fumes) can accumulate.

Protective equipment:

Firefighters should wear NFPA compliant firefighting protective equipment, including self-contained breathing apparatus and helmet, hood, boots, and gloves. Avoid contact with product. Decontaminate equipment and protective clothing prior to reuse. If material is spilled or released and exposure likely, evacuate area and fight fire from a safe distance or a protected location.

Additional information:

Due to reaction of water producing CO₂ gas, a hazardous build-up of pressure could result if contaminated containers are re-sealed. Containers may burst if overheated.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:

No action shall be taken involving any personal risk without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).

Environmental precautions:

Do not discharge into drains/surface waters/groundwater.

Methods and material for containment and cleaning up:

Absorb isocyanate with suitable absorbent material: Dirt, Vermiculite, Sand, Clay.

Ensure adequate ventilation.

Contain spilled material if possible. Shovel into open container. Do not make container pressure tight. Move container to a well-ventilated area (outside). Spill area can be decontaminated with the following recommended decontamination solution: Mixture of 90 % water, 8 % concentrated ammonia, 2 % detergent. Add about 10 parts of decontamination solution per part of isocyanate, with mixing. Allow substance to evaporate. See Section 13 for additional information.

Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7. HANDLING AND STORAGE

Handling:**Precautions for safe handling:**

Ensure good ventilation/exhaustion at the workplace.

Avoid contact with eyes and prolonged or repeated contact with skin.

Wash thoroughly after handling.

SAFETY DATA SHEET

Staycell ONE STEP® 502 A-Isocyanate

Information about protection against explosions and fires:

No special measures required.

Conditions for safe storage, including any incompatibilities:

Requirements to be met by storerooms and receptacles:

No special requirements.

Information about storage in one common storage facility:

Store in a dry place. Protect from atmospheric moisture. Do not store near water – contaminated product can result in potentially hazardous reaction.

Further information about storage conditions:

Keep drum tightly sealed.

Storage period: 6 months

Storage temperature: 50° to 85°F.

Specific end use(s):

See technical data sheet for details

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters:

Diphenylmethane-4,4'-diisocyanate (MDI) (CAS No. 101-68-8)

OSHA	Ceiling: 0.02 ppm, 0.2mg/m ³
------	---

Polymeric Diphenylmethane Diisocyanate (pMDI) (CAS No. 9016-87-9)

OSHA	Ceiling: 0.02 ppm, 0.2mg/m ³
------	---

Exposure controls

Personal protective equipment:



General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Wash contaminated clothing before reuse.

Ensure that eyewash stations and safety showers are close to the workstation area.

Breathing equipment:

In case of brief exposure at low atmospheric levels, use an approved air-purifying respirator equipped with an organic vapor sorbent and particle filter. In case of intensive or longer exposure, use a positive pressure air-supplying respirator (air line or self-contained breathing apparatus).

Protection of hands:

The workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture

SAFETY DATA SHEET

Staycell ONE STEP® 502 A-Isocyanate

protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Material of gloves:

Use chemical resistant gloves classified under Standard EN374: Protective gloves against chemicals and microorganisms. Examples of preferred glove barrier materials include: Butyl rubber, Polyethylene, EVAL, Neoprene, Nitrile, Viton. When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher is recommended.

Penetration time of glove material:

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye Protection:

Tightly sealed chemical goggles consistent with EN 166 or equivalent. Wear a face-shield which allows use of chemical goggles or wear full-face respirator to protect face and eyes when there is any likelihood of splashes.

Body Protection:

Personal protective clothing for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Safety glasses with side shields or goggles recommended. If there is a potential for splashing, use full face shield over safety glasses or goggles.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:

Form: Liquid

Color: Amber

Odor: Musty

Odor Threshold: Not determined

pH-value: Not determined

Boiling Point: 200°C (392°F)

Flash Point: 200°C (392°F)

Flammability (solid, gaseous): Not determined

Decomposition Temperature: Not determined

Explosion Limits:

Lower: Not determined

Upper: Not determined

Vapor Pressure: < 0.00001 mmHg@25°C

Vapor Density: Heavier than air

Evaporation Rate: Slower than ether

Solubility in Water: Insoluble

Partition coefficient (n-octanol/water): Not determined

10. STABILITY AND REACTIVITY

Chemical Stability & Reactivity:

Stable under normal conditions of storage and use.

Thermal Decomposition/Conditions to be Avoided:

No decomposition if used according to specifications.

Possibility of Hazardous Reactions:

Contact with moisture or temperatures above 177°C (350°F) can cause pressure build-up and possible rupture of closed containers. Product is insoluble with, and heavier than, water and sinks to the bottom but reacts slowly at the interface.

SAFETY DATA SHEET

Staycell ONE STEP® 502 A-Isocyanate

Conditions To Avoid:

Extremes of temperatures and direct sunlight. Exposure to air or moisture over prolonged periods.

Incompatible Materials:

Acids, alcohols, amines, strong bases and moisture/water

Hazardous Decomposition Products:

By fire and high heat: Carbon oxides (CO, CO₂), nitrogen oxides (NO, NO₂), isocyanates, isocyanic acid and other undetermined compounds.

11. TOXICOLOGICAL INFORMATION

Routes of Exposure:

Skin, inhalation

Acute Toxicity – Inhalation:

Assessment: The substance/mixture is not toxic on inhalation as defined by dangerous good regulations.

Acute toxicity estimate (LC50): >2.2 mg/L

Exposure time: 1 hour

Method: Calculation method

Remarks: Methods used to generate exposure concentrations in animal studies use extreme laboratory conditions and does not represent actual exposure conditions of the material in the workplace, storage, transportation or expected use on the market due to the very low vapor pressure.

Symptoms related to physical, chemical and toxicological characteristics:

Minor skin irritation

Asthma-like symptoms

Delayed and immediate effects and chronic effects from short and long-term exposure:

Possible sensitization

12. ECOLOGICAL INFORMATION

Ecotoxicity:	LC0:>1,000mg/l (Zebra fish 96 hrs) LC0: >3,000mg/l (Killifish 96 hrs)
Persistence and degradability:	0%
Bioaccumulative potential	Does not bioaccumulate

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Recommendation:

The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of all federal, state and local environmental protections and waste disposal regulations. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Uncleaned Packagings:

Recommendation:

Disposal must be made according to official regulations.

SAFETY DATA SHEET

Staycell ONE STEP® 502 A-Isocyanate

14. TRANSPORT INFORMATION

U.S. DOT Information:

Not regulated

IMDG Information:

Not regulated

IATA Information:

Not regulated

15. REGULATORY INFORMATION

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical Name	CAS Number	SARA 313 – Threshold Values %
Polymeric Diphenylmethane Diisocyanate (pMDI)	9016-87-9	1.0
Diphenylmethane-4,4'-diisocyanate (MDI)	101-68-8	1.0

SARA 311/312 Hazard Categories:

Acute health hazard: Yes

Chronic health hazard: Yes

Fire hazard: No

Sudden release of pressure hazard: No

Reactive hazard: No

CWA – Clean Water Act: This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and CFR 122.42).

CERCLA: This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

Chemical Name	CAS Number	CERCLA/SARA RQ	Reportable Quantity (RQ)
Diphenylmethane-4,4'-diisocyanate (MDI)	101-68-8	-	5,000 LB

U.S. State Regulations

California Proposition 65: This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations:

Chemical Name	CAS Number	New Jersey	Massachusetts	Pennsylvania
Polymeric Diphenylmethane Diisocyanate (pMDI)	9016-87-9	X	-	-
Diphenylmethane-4,4'-diisocyanate (MDI)	101-68-8	X	X	X

16. OTHER INFORMATION

Department Issuing SDS:

Preferred Solutions, Inc. Product Stewardship



SAFETY DATA SHEET

Staycell ONE STEP® 502 A-Isocyanate

Date of Preparation/Last Revision:

5/28/25

Abbreviations and Acronyms:

IMDG: International Maritime Code of Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

NFPA: National Fire Protection Agency (USA)

HMIS: Hazardous Materials Identification System (USA)

CSR: Chemical Safety Report

SDS: Safety Data Sheet

MSDS: Material Safety Data Sheet

PBT: Persistent, Bioaccumulative and Toxic Substances

STEL: Short-Term Exposure Limit

TLV: Threshold Limit Value

TWA: Time Weighted average

vPvB: Very Persistent and Very Bioaccumulative

LC50: Lethal Concentration, 50 percent

LD50: Lethal Dose, 50 percent

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.